


Specifications:

Current Rating:2.0A AC/DC
 Voltage Rating:250V AC/DC
 Contact Resistance:20m ohm max.
 Withstanding Voltage:500V AC/minute
 Insulation Resistance:1000M ohm min.
 Operating Temperature Rating:-40°C ~ +105°C
 Materials:

Insulator:High Temp.Plastic(UL94V-0)
 Insulator Color:Black
 Contact :Brass
 Finish:Gold Plated

How To Order
 PHVD20-XXG-820AH15

H15:Insulator 1.5mm
 Pin Length 14.1mm
 G:Gold Plated
 T: Tin Plated
 SG:Selective Gold Plated
 No. Of Positions
 VD: Straight Type



PCB Layout

RoHS Compliant

F				DRAWN:	GENERAL TOLERANCE:		DESCRIPTION:	SIZE
E				Ken	.X=±0.20 .XX=±0.15			
D				CHECKED:	UNIT: MM	2.0m Pin Header Straight Type	A4	
C				Lily Chou	SCALE: 1:1			
B				APPROVAL:	SHEET: 1 / 1	PART NO:		
A	16-Jul-2020	(PC0001)	Ken	Chao Peng	PROJECTION:	PHVD20-XXX-820AH15		
REV	DATE	FILE	BY					