


Specifications:
 Current rating:1.0A AC,DC
 Voltage rating:150V AC,DC
 Contact resistance:30m ohm.Max
 Insulation resistance:500M ohm.Min
 Withstanding voltage:250V AC/minute
 Operating temperature range:-40°C~+85°C
 Material:
 Insulator:High Temp. Plastic(PA46 UL94V-0)
 Insulator Color:Ivory
 Contact:Brass
 Plated:Tin Plated
 How To Order:
 WFV125-XX
 ————— No. of Positions
 ————— V: Straight Type

Ordering Information & Dimensions

Pin No	Dimensions		Pin No	Dimensions	
	A	B		A	B
02P	1.25	3.75	09P	10.00	12.50
03P	2.50	5.00	10P	11.25	13.75
04P	3.75	6.25	11P	12.50	15.00
05P	5.00	7.50	12P	13.75	16.25
06P	6.25	8.75	13P	15.00	17.50
07P	7.50	10.00	14P	16.25	18.75
08P	8.75	11.25	15P	17.50	20.00



RoHS Compliant

F				DRAWN: Ken	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15		DESCRIPTION: 1.25mm Wafer Straight Type	SIZE A4
E				CHECKED: Lily Chou	UNIT: MM SCALE: 1:1			
D				APPROVAL: Chao Peng	SHEET: 1 / 1	PART NO: WFV125-XX		
C					PROJECTION:			
B								
A	01-SEP-2009	(H0087)	Ken					
REV	DATE	FILE	BY					