


HST10XX-LK

Specifications:
 Current Rating:14.0A AC/DC
 Voltage Rating:400V AC/DC
 Contact Resistance:10m ohm. Max.
 Insulation Resistance:1000M ohm. Min.
 Withstanding Voltage:1.800V AC/Minute
 Operating Temperature Range:-40°C~+105°C
 Material and Finish
 Insulator:Nylon 4T UL94V-0
 Color:Black
 Contact:Phosphor Bronze
 Plating:Gold Plated
 Recommended Insulator



How To Order
 HSA10-XX-LK

└── LK:With Lock
 └── No. Of Positions

Circuits	A	B	C
06	7.7	5.0	6.4
07	8.7	6.0	7.4
08	9.7	7.0	8.4
09	10.7	8.0	9.4
10	11.7	9.0	10.4
11	12.7	10.0	11.4
12	13.7	11.0	12.4
13	14.7	12.0	13.4
14	15.7	13.0	14.4
15	16.7	14.0	15.4

RoHS Compliant

E				DRAWN: Ken	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15		DESCRIPTION: 1.0mm Female Housing With Lock & Terminal	SIZE A4
D				CHECKED: Lily Chou	UNIT: MM			
C					SCALE: 1:1			
B					SHEET: 1 / 2			
A	16-Aug-2021	(PC0001)	Ken	APPROVAL: Chao Peng	PROJECTION:	PART NO:	HSA10-XX-LK &HST10XX	
REV	DATE	FILE	BY					