


Specifications:

Current Rating:1A AC/DC
 Voltage Rating:60V AC/DC
 Contact Resistance:5m ohm. Max.
 Insulation Resistance:100M ohm. Min.
 Withstanding Voltage:500V AC/Minute
 Waterproof rate:IP67
 Operating Temperature Range:-25°C ~ +90°C
 Material and Finish
 Insulator:TPU/PA+GF
 Contact:Brass Gold Plated
 Nut/Screw:Brass Nickel Plated
 Connector Overmold:TPU
 Seal/O-ring:Epoxxy resin/FKM

How to Order
 MCM5-XM01



Contact Configuration:

Pin	Contacts		Contacts Termination	Wire gauge /size	
	Socket	Plug		AWG	mm2
3Pin (A Coding)			Solder	26	0.14
4Pin (A Coding)			Solder	26	0.14

RoHS Compliant

F				DRAWN: ANDREW	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15 .XXX=±0.10		DESCRIPTION: M5 Cable Assemble Straight Type Connector	SIZE
E								
D				CHECKED: BILLHE	UNIT: MM	PART NO: MCM5-XM01	A4	
C					SCALE: 1:1			
B				APPROVAL: NORMAN	SHEET: 1/1			
A	21-MAR-2019	(PC0001)	ANDREW		PROJECTION:			
REV	DATE	FILE	BY					