

Pin No.	Dim A	Dim B	Pin No.	Dim A	Dim B	Pin No.	Dim A	Dim B	Pin No.	Dim A	Dim B
04	1.27	2.94	24	13.97	15.64	44	26.67	28.34	64	39.37	41.04
06	2.54	4.21	26	15.24	16.91	46	27.94	29.61	66	40.64	42.31
08	3.81	5.48	28	16.51	18.18	48	29.21	30.88	68	41.91	43.58
10	5.08	6.75	30	17.78	19.45	50	30.48	32.15	70	43.18	44.85
12	6.35	8.02	32	19.05	20.72	52	31.75	33.42	72	44.45	46.12
14	7.62	9.29	34	20.32	21.99	54	33.02	34.69	74	45.72	47.39
16	8.89	10.56	36	21.59	23.26	56	34.29	35.96	76	46.99	48.66
18	10.16	11.83	38	22.86	24.53	58	35.56	37.23	78	48.26	49.93
20	11.43	13.10	40	24.13	25.80	60	36.83	38.50	80	49.53	51.20
22	12.70	14.37	42	25.40	27.07	62	38.10	39.77			

Specifications:

Current rating:1.0A AC/DC

Voltage rating:50V AC/DC

Contact resistance:20m ohm max

Insulation Resistance:500M ohm min

Withstanding voltage:500V AC/minute

Operating Temperature range:-25°C to +105°C

Material:

Insulator:High Temp.Plastic(Nylon 6T UL94V-0)

Insulator Color:Black


Contact:Copper Alloy

Plated:Gold Plated


Package:1500pcs/Reel

How To Order

PSDSM127-XXG-23-CR



Cap+Tape&Reel  
Total Height:2.3mm  
G:Gold Plating  
NO.OF Contacts  
Double Row SMT Type



P.C.B Layout

RoHS Compliant

F				DRAWN:	GENERAL TOLERANCE:		DESCRIPTION: 1.27mm PCB Socket 2.3mm Height SMT Type	SIZE <b>A4</b>
E				Ken	.X=±0.20 .XX=±0.15			
D				CHECKED:	UNIT: MM	PART NO: PSDSM127-XXG-23-CR		
C				Lily Chou	SCALE: 1:1			
B				APPROVAL:	SHEET: 1 / 1			
A	01-SEP-2009	(PC0001)	Ken	Chao Peng	PROJECTION:			
REV	DATE	FILE	BY					