

Specifications:

Current rating:2.0A AC/DC

Voltage rating:250V AC/DC

Contact resistance:20m ohm max.

Withstanding Voltage:500V AC/minute

Insulation resistance:1000M ohm min.

Operating Temperature Rating:-40°C ~ +105°C

Materials:

Insulator:High Temp Plastic (Nylon 6T UL94V-0)

Insulator Color:Black

Contact:Phosphor Bronze

Finish:Gold Plated

How To Order

PSRD20-XXG-H40

Height 4.0mm


Gold Plated

No.of Positions

RD:Right Angle Double Row



Dimension :

Circuits	A	B	Circuits	A	B	Circuits	A	B	Circuits	A	B
04	4.50	2.00	24	24.50	22.00	44	44.50	42.00	64	64.50	62.00
06	6.50	4.00	26	26.50	24.00	46	46.50	44.00	66	66.50	64.00
08	8.50	6.00	28	28.50	26.00	48	48.50	46.00	68	68.50	66.00
10	10.50	8.00	30	30.50	28.00	50	50.50	48.00	70	70.50	68.00
12	12.50	10.00	32	32.50	30.00	52	52.50	50.00	72	72.50	70.00
14	14.50	12.00	34	34.50	32.00	54	54.50	52.00	74	74.50	72.00
16	16.50	14.00	36	36.50	34.00	56	56.50	54.00	76	76.50	74.00
18	18.50	16.00	38	38.50	36.00	58	58.50	56.00	78	78.50	76.00
20	20.50	18.00	40	40.50	38.00	60	60.50	58.00	80	80.50	78.00
22	22.50	20.00	42	42.50	40.00	62	62.50	60.00			



P.C.B. Layout

RoHS Compliant

F				DRAWN:	GENERAL TOLERANCE:			SIZE
E				Ken	.X=±0.20 .XX=±0.15			
D				CHECKED:	UNIT: MM	DESCRIPTION: 2.0mm PCB Socket Double Row Right Angle Type		A4
C				Lily Chou	SCALE: 1:1			
B				APPROVAL:	SHEET: 1 / 1	PART NO: PSRD20-XXG-H40		
A	01-SEP-2009	(PC0001)	Ken	Chao Peng	PROJECTION: 			
REV	DATE	FILE	BY					