

1

2

3

4

5

RECOMMENDED PCB LAYOUT

RoHS Compliant

Specifications:

Current Rating:1.0A AC/DC

Voltage Rating:30V AC

Contact Resistance:50m ohm. Max.

Insulation Resistance:100M ohm. min.

Withstanding Voltage:100V AC For One Minute

Operating Temperature Range:-40°C ~ +105°C

Material and Finish

Insulator:High Temp. Plastic (LCP UL94V-0)

Insulator Color:Black

Contact:Phosphor Bronze

Plating:Gold Plated

Shell:Brass,Nickel Plated

How To Order

UBSRSM-08A2-TR

TR:Tape & Reel

A2 Type

No. Of Positions

R/A SMT Type

A

B

C

D

E				DRAWN:	Jack Zhou	GENERAL TOLERANCE:	.X=±0.2 .XX=±0.15		DESCRIPTION: Mini USB Sokcet 8P R/A SMT Type	SIZE A4
D				CHECKED:	Ken Wang	UNIT: MM				
C						SCALE:2:1				
B						SHEET: 1 / 1				
A	04-Sep-2016	(H0001)	Jack Zhou	APPROVAL:	Make Hu	PART NO:	UBSRSM-08A2-TR			
REV	DATE	FILE	BY			PROJECTION:				