

Dimension Information:

Circuits	Dim A	Dim B	Circuits	Dim A	Dim B
2	4.2	5.4	14	25.2	30.6
4	4.2	9.6	16	29.6	34.8
6	8.4	13.8	18	33.6	39.0
8	12.6	18.0	20	37.8	43.2
10	16.8	22.2	22	42.0	47.4
12	21.0	26.4	24	46.2	51.6



Specifications:

Current Rating:9.0A AC/DC  
 Voltage Rating:600V AC/DC  
 Contact Resistance:10m ohm. Max.  
 Insulation Resistance:1000M ohm. Min.  
 Withstanding Voltage:600V AC For One Minute  
 Operating Temperature Range:-40°C To +105°C  
 Materials:

Insulator:High Temp. Plastic(Nylon66 UL94V-0)  
 Insulator Color:White  
 Contact:Brass  
 Plating:Tin Plated

How To Order

WFDV42-XX



RECOMMENDED P.C.B. LAYOUT

RoHS Compliant

F				
E				
D				
C				
B				
A	22-May-2014	(H0030)	Ken	
REV	DATE	FILE	BY	

DRAWN: Ken	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15
CHECKED: Lily Chou	
APPROVAL: Chao Peng	UNIT: MM
	SCALE: 1:1
	SHEET: 1 / 2
	PROJECTION:

		DESCRIPTION:	SIZE
		4.2mm Wafer Straight Type	<b>A4</b>
PART NO:	WFDV42-XX		