

Specifications:

Current rating:2.0A AC,DC
 Voltage rating:125V AC,DC
 Contact resistance:20m ohm.Max
 Insulation resistance:1000M ohm.Min
 Withstanding voltage:500V AC/minute
 Operating temperature range:-40°C~+85°C

Material:


Insulator:Nylon 66 (UL94V-0)
 Default Color:White
 Contact:Brass
 Plated:Tin Plated

How To Order:
 WFRJ20-XX

— No. of Contacts
 — RJ:Right Angle

Dimension:

Circuits	Dimension:		Circuits	Dimension:	
	A	B		A	B
02	2.00	6.00	10	18.00	22.00
03	4.00	8.00	11	20.00	24.00
04	6.00	10.00	12	22.00	26.00
05	8.00	12.00	13	24.00	28.00
06	10.00	14.00	14	26.00	30.00
07	12.00	16.00	15	28.00	32.00
08	14.00	18.00	16	30.00	34.00
09	16.00	20.00			



PCB Layout

F				DRAWN: Ken	GENERAL TOLERANCE: .X=±0.20 .XX=±0.15	HOYATO 东莞好亚通电子厂 Connector supplies	DESCRIPTION: 2.0mm Wafer Single Row R/A Type	SIZE A4
E								
D				APPROVAL: Chao Peng	SCALE: 1:1	PART NO: WFRJ20-XX		
C					PROJECTION:			SHEET: 1 / 1
B								
A	01-SEP-2009	(PC0001)	Ken					
REV	DATE	FILE	BY					