



Specifications:

Current Rating:3.0A AC/DC
 Voltage Rating:250V AC/DC
 Contact Resistance:15m ohm. max.
 Insulation Resistance:1000M ohm. Min.
 Withstanding voltage:600V AC For One Minute
 Operating Temperature Range:-25°C to +105°C
 Material and Finish
 Insulator:Nylon 66 UL94V-0
 Contact:Copper Alloy
 Plating:Gold Plated
 How To Order
 HA254-XX

└── No. of Positions
 └── A:Single Rows

Dimension

Circuits	Dimention		Circuits	Dimention	
	Dim.A	Dim.B		Dim.A	Dim.B
02	2.54	5.08	14	33.02	35.56
03	5.08	7.62	15	35.56	38.10
04	7.62	10.16	16	38.10	40.64
05	10.16	12.70	17	40.64	43.18
06	12.70	15.24	18	43.18	45.72
07	15.24	17.78	19	45.72	48.26
08	17.78	20.32	20	48.26	50.80
09	20.32	22.86	21	50.80	53.34
10	22.86	25.40	22	53.34	55.88
11	25.40	27.94	23	55.88	58.42
12	27.94	30.48	24	58.42	60.96
13	30.48	33.02	25	60.96	63.50

RoHS Compliant

F			
E			
D			
C			
B	18-Jun-2020	Amend Dim	Ken
A	01-SEP-2009	(QC01)	Ken
REV	DATE	FILE	BY

DRAWN: Ken
 CHECKED: Lily Chou
 APPROVAL: Chao Peng

GENERAL TOLERANCE:
 .X=±0.20
 .XX=±0.15
 UNIT: MM
 SCALE: 1:1
 SHEET: 1 / 1
 PROJECTION:



DESCRIPTION: 2.54mm Housing
 Single Row + Terminal
 PART NO: HA254-XX & HAT254T

SIZE
A4