


PCB Layout

Specifications:  
 Current rating:3.0A AC/DC  
 Voltage Rating:250V AC/DC  
 Contact Resistance:20m ohm Max  
 Insulation Resistance:1000M ohm Min  
 Withstanding Voltage:600V AC For one Minute  
 Operating Temperature Range:-40°C To +105°C  
 Materials and Finish  
 Insulator:PBT(UL94V-0)  
 Insulator Color:Black  
 Contact:Copper Alloy  
 Plating:Gold Plated,Tin Plated  
 How To Order  
 PHVD254-XXX-1600

Pin Length  
 G:Gold Plated  
 T:Tin Plated  
 No.Of Positions  
 Straight Type

RoHS Compliant

F				DRAWN:	GENERAL TOLERANCE:		DESCRIPTION: 2.54mm Pin Header Double Row Straight Type	SIZE <b>A4</b>
E			Ken	.X=±0.20 .XX=±0.15				
D			CHECKED:	UNIT: MM				
C			Lily Chou	SCALE: 1:1				
B			APPROVAL:	SHEET: 1 / 1				
A	27-May-2023	(PC0001)	Ken	Chao Peng	PROJECTION:	PART NO:	PHVD254-XXX-1600A	
REV	DATE	FILE	BY					